Glannu

PRODUCT DATASHEET
GEV-7230

EV 2-WHEELER BATTERY · SMART NMC

Lithium-ion Battery Pack

72V 30Ah

74 V · 30 Ah · 2,220 Wh

FRP FIRE-RESISTANT CASE **20S 80A SMART BMS**

74 V Nominal voltage	**30 Ah** Capacity	**2.2 kWh** Energy
55–75 km Typical range*	**50 A** Max continuous	**20S6P** Configuration



Representative image - case and connector vary by model and vehicle

Key Features

- **High Energy Density** — 120 graded 21700 5 Ah NMC cells, 20S6P
- **Smart BMS Protection** — Over/under-voltage, over-current, short-circuit and temperature protection
- **FRP Fire-Resistant Case** — Fire-retardant enclosure for safer on-vehicle use
- **Cell Balancing** — Keeps cells matched for longer life and full usable capacity
- **Fits Your Vehicle** — Standard sizes, or built to your scooter's battery bay
- **Fast, Safe Charging** — CC-CV to 84 V; SB50 output, Elcom charging port

Applications

Electric scooters | E-bikes & e-mopeds | E-motorcycles | Delivery & fleet EVs | EV battery upgrades

For 72V low- and high-speed two-wheelers. *Range is typical at 30–40 Wh/km and varies with motor, load, speed and road.

DIMENSIONS & WEIGHT

Standard (W x L x H)	Built to your vehicle - confirmed with the quote
Custom size	Made to fit your battery bay on request

Weight ≈ 11.3 kg · Output: SB50 · Charging: Elcom

DESIGNED TO STANDARDS

IEC 62133-2:2017
IS 16046-2018
UN38.3 (transport)

Recommended Charger Settings

Li-ion NMC Battery type	**84 V** Charge voltage	**6 A (0.2C)** Standard current	**10 A** Max current	**1.5 A (0.05C)** Charge cut-off	**0 – 45 °C** Charge temp.

Call **+91 70838 98947** · WhatsApp **+91 82619 63374** · Email **info@glannu.com** · Shop online **store.glannu.com**

Glannu Industries · Sargam B, B-1808, Nanded City, Sinhgad Rd, Pune, Maharashtra 411068

Specifications subject to change · © 2026 Glannu Industries

Glannu

PRODUCT DATASHEET

GEV-7230


Technical Specifications

GENERAL	
Product	Lithium-ion EV Battery Pack 72V 30Ah
Model no.	GEV-7230
Chemistry	Lithium-ion NMC
Cell	21700 cylindrical, 3.7 V 5.0 Ah
Configuration	20S6P (120 cells)
ELECTRICAL	
Nominal voltage	74 V (72 V class)
Nominal capacity	30 Ah
Nominal energy	2,220 Wh
Voltage range	56 – 84 V (2.8 – 4.2 V/cell)
Charge efficiency	≥ 98%
Cycle life	≥ 800 cycles @ 80% DoD
CHARGE	
Charging method	CC–CV
Charge voltage	84 V
Standard charge current	6 A (0.2C)
Max charge current	10 A
Charge cut-off current	1.5 A (0.05C)
DISCHARGE	
Standard discharge current	15 A (0.5C)
Max continuous discharge	50 A (BMS limited)
Discharge cut-off voltage	56 V
BMS & PROTECTION	
BMS	20S 80 A smart BMS, cell balancing
Over-voltage	4.20 V/cell (84 V); recovery 4.00 V/cell
Under-voltage	2.80 V/cell (56 V); recovery 3.00 V/cell
Charge over-current	10 A
Short circuit	Protected
Over-temp. (discharge)	60 °C; recovery 50 °C
Over-temp. (charge)	50 °C; recovery 40 °C
ENVIRONMENT	
Discharge temperature	-10 °C to +55 °C
Charge temperature	0 °C to +45 °C
Storage temperature	0 °C to +35 °C
Humidity	< 90% RH, non-condensing
MECHANICAL	
Dimensions (W x L x H)	Built to vehicle (on request)
Weight	≈ 11.3 kg
Enclosure	FRP fire-resistant case
Connectors	SB50 output, Elcom charging port
STANDARDS	
Safety (design)	IEC 62133-2:2017 / IS 16046-2018
Transport	UN38.3
Documents	MSDS available on request


SAFETY & HANDLING

- Charge only with a Li-ion charger set to 84 V; do not leave on charge indefinitely.
- Do not wet, crush, puncture, heat, disassemble or short the terminals.
- Store dry and ventilated at 20–35 °C, away from sunlight; at 40–60% charge for long storage.
- Never reverse polarity. Dispose of as per government e-waste rules.


Typical Discharge Curves



Charging Profile (CC–CV)



Cycle Life



Charts show typical NMC behaviour at 25 °C for this 20S6P pack and are for reference only. Actual results depend on temperature, load and charger.

Need a pack for your vehicle?

Send your scooter model and battery-bay size.

Call us
+91 70838 98947

WhatsApp us
+91 82619 63374

Specifications subject to change · © 2026 Glannu Industries